

GEOSTATS PTY LTD

Mining Industry Consultants
Reference Material Manufacture and Sales

Certified Geochem Base Metal Reference Material Product Code

GBM323-6

Certified Control Values

Total Digest

Element	Grade	Standard Deviation	Num of Analyses	Confidence Interval
Nickel (ppm)	36	3	61	+/- 0.8
Copper (ppm)	5353	181	64	+/- 45.7
Zinc (ppm)	388	17	63	+/- 4.2
Lead (ppm)	112	7	61	+/- 1.7
Arsenic (ppm)	39	2	48	+/- 0.6
Cobalt (ppm)	72	3	58	+/- 0.8
Silver (ppm)	1.8	0.2	54	+/- 0.05

Partial Digest

Element	Grade	Standard Deviation	Num of Analyses	Confidence Interval
Nickel (ppm)	23	1	48	+/- 0.4
Copper (ppm)	5377	174	73	+/- 40.9
Zinc (ppm)	362	15	59	+/- 4.1
Lead (ppm)	108	5	58	+/- 1.4
Arsenic (ppm)	39	4	57	+/- 0.9
Cobalt (ppm)	60	4	53	+/- 1.2
Silver (ppm)	1.8	0.2	61	+/- 0.05

CRM Details

Control Statistic Details		Neutron Activation Analysis Results (ppm, unless otherwise noted)		Major Elements by Fusion / XRF (%)	
Control statistics were produced from results accumulated in the April-2023 round robin. The number of results used to certify each analyte is shown in the table above.		Antimony	1.2	Fe	5.78
		Arsenic	40	SiO ₂	60.43
		Barium	417	Al ₂ O ₃	13.93
		Bromine	<2	TiO ₂	1.198
		Cadmium	<10	MnO	0.11
		Caesium	2	CaO	5.84
		Calcium (%)	nr	P	0.062
		Cerium	41	S	0.673
		Chromium	95	MgO	3.06
		Cobalt	75	K ₂ O	1.93
		Europium	1.2	Na ₂ O	3.115
		Gold (ppb)	831	LOH1000	0.66
		Hafnium	<5	Neutron Activation Analyses and Fusion / XRF Analyses are single results and are indicative only. These are provided for matrix identification purposes. 'nr': Not Reported	
		Iridium (ppb)	<50		
		Iron (%)	6		
		Lanthanum	20		
		Lutetium	0.4		
		Mercury	nr		
		Molybdenum	<10		
		Neodymium	nr		
		Nickel	<100		
		Potassium (%)	nr		
		Rubidium	89		
		Samarium	4.7		
		Scandium	18.9		
		Selenium	<10		
		Silver	<5		
		Sodium (%)	2.17		
		Strontium	nr		
		Tantalum	<2		
		Tellurium	<20		
		Terbium	<1		
		Thorium	11.7		
		Tin	<200		
		Tungsten	<2		
		Uranium	6		
		Ytterbium	2.9		
		Zinc	380		
		Zirconium	<500		

Material Description This material is described as a Copper sulphide ore.	
Colour Designation (ISCC-NBS, SP440) This material is medium light gray in colour.	
Usage This product is for use in the mining industry as a reference material for monitoring and testing the accuracy of laboratory assaying.	
Preparation and Packaging All CRMs are dried in an oven for a minimum of 12 hours at 110°C. The dry material is then pulverised to better than 75 micron (nominal mean of 45 micron) using an air classifier. The material is then homogenised and stored in a sealed, stable container ready for final packaging. Materials are statistically sampled from stores, then packaged into either heat sealed, air tight, plastic pulp packets or screw top sealed plastic containers ready for distribution. All packaging has been chosen to ensure minimal contamination from outside sources during shipment, use and storage.	
Assay Testwork All standards are tested thoroughly in the Geostats bi-annual laboratory survey. This involves assaying by multiple laboratories from around the world. Results are compiled into a comprehensive report detailing statistics for each standard. Assay distributions are checked and processed statistically, producing monitoring statistics for these standards. Materials are tested regularly to ensure stability and homogeneity.	
Stability This product remains stable in its original packaging, away from direct sunlight.	
Material Safety This product is not hazardous and non-toxic.	

20 Hines Road, O'Connor, Western Australia 6163

Phone: +61 8 9314 2566 | Email: info@geostats.com.au

Website: www.geostats.com.au

GBM323-6

Geostats Pty Ltd, Certified Geochem Base Metal Reference Material, Product Code: