

GEOSTATS PTY LTD

Mining Industry Consultants
Reference Material Manufacture and Sales

Certified Ore Grade Base Metal Reference Material Product Code

GBM904-16

Certified Control Values

Ore Grade Base Metal Analyses

Element	Grade	Standard Deviation	No of Analyses	Confidence Interval
Nickel (ppm)	22435	913	43	+/- 284
Copper (ppm)	11773	555	35	+/- 194
Zinc (ppm)	164	82	25	+/- 35
Lead (ppm)	61	33	15	+/- 19
Cobalt (ppm)	nr	nr	nr	nr
Silver (ppm)	nr	nr	nr	nr
Sulphur (%)	nr	nr	nr	nr

CRM Details

Control Statistic Details

Control statistics were produced from results accumulated in the :

October-2004 Geostats Pty Ltd Laboratory Round Robin Program.
15 laboratories (at least) tested this material for base metal content.

Source Material

Prior to homogenisation and testing, this material was sourced from Nickel Sulphide Ore High Iron

Colour Designation

Dark gray

Usage

This product is for use in the mining industry as reference materials for monitoring and testing the accuracy of laboratory assaying.

Preparation and Packaging

All standards are dried in an oven for a minimum of 12 hours at 110C. The dry material is then pulverised to better than 75 micron (nominal mean of 45 micron) using an Air Classifier. The material is then homogenised and stored in a sealed, stable container ready for final packaging.

Materials are statistically sampled from stores, then packaged into either heat sealed, air tight, plastic pulp packets or screw top sealed plastic containers ready for distribution. All packaging has been chosen to ensure minimal contamination from outside sources during shipment, use and storage.

Assay Testwork


All standards are tested thoroughly in the Geostats bi-annual laboratory survey. This involves assaying by a minimum of 50 reputable laboratories selected from across the world using a variety of methods (including AR, 3AD, 4AD and ICP, AAS and XRF). Results are compiled into a comprehensive report detailing statistics for each standard. Assay distributions are checked and processed statistically, producing monitoring statistics for these standards. Materials are tested regularly to ensure stability and homogeneity.

Neutron Activation Analysis Results (ppm)

Antimony	0.2
Arsenic	1.9
Barium	110
Bromine	<0.5
Cadmium	<7
Cerium	13
Caesium	<0.5
Chromium	66
Cobalt	1220
Europium	<1
Gold ppb	52
Hafnium	1
Iridium ppb	<50
Iron %	41.2
Lanthanum	10
Lutetium	0.4
Molybdenum	<3
Nickel	23700
Rubidium	<14
Samarium	2.3
Scandium	11
Selenium	35
Sodium %	0.17
Tantalum	0.5
Tellurium	<10
Terbium	0.8
Thorium	2.7
Tin	<100
Tungsten	<2
Uranium	<0.2
Ytterbium	<2
Zinc	<100
Zirconium	<200
Calcium%	nr
Potassium %	nr
Silver	nr
Mercury	nr
Neodymium	nr
Strontium	nr

Major Elements Fusion / XRF (%)

Fe	nr
SiO2	nr
Al2O3	nr
TiO2	nr
MnO	nr
CaO	nr
P	nr
S	nr
MgO	nr
K2O	nr
Na2O	nr
LOI1000	nr



10A Marsh Close, O'Connor, Western Australia 6163

Phone : +61 8 9314 2566, Fax : +61 8 9314 3699

e-mail : pjh@geostats.com.au, srr@geostats.com.au

Website <http://www.geostats.com.au>

GBM904-16

Geostats Pty Ltd, Certified Base Metal Reference Material, Product Code :