


GEOSTATS PTY LTD

Mining Industry Consultants
Reference Material Manufacture and Sales

Certified Ore Grade Base Metal Reference Material Product Code

GBM919-13

Certified Control Values



Element	Grade	Standard Deviation	Num of Analyses	Confidence Interval
Nickel (ppm)	56	7	81	+/- 2
Copper (ppm)	16692	595	165	+/- 87
Zinc (ppm)	65874	3012	151	+/- 488
Lead (ppm)	3986	182	144	+/- 26
Cobalt (ppm)	nr	nr	nr	nr
Silver (ppm)	17.3	1.1	101	+/- 0.22
Sulphur (%)	5.78	0.20	100	+/- 0.04

CRM Details

Control Statistic Details

Control statistics were produced from results accumulated in the October-2007, October-2019 round robins. The number of results used to certify each analyte is shown in the table above.

Material Description

This material is described as a Low grade Copper / Zinc sulphide Ore.

Colour Designation (ISCC-NBS, SP440)

This material is light gray in colour.

Usage

This product is for use in the mining industry as a reference material for monitoring and testing the accuracy of laboratory assaying.

Preparation and Packaging

All CRMs are dried in an oven for a minimum of 12 hours at 110°C. The dry material is then pulverised to better than 75 micron (nominal mean of 45 micron) using an air classifier. The material is then homogenised and stored in a sealed, stable container ready for final packaging.

Materials are statistically sampled from stores, then packaged into either heat sealed, air tight, plastic pulp packets or screw top sealed plastic containers ready for distribution. All packaging has been chosen to ensure minimal contamination from outside sources during shipment, use and storage.

Assay Testwork

All standards are tested thoroughly in the Geostats bi-annual laboratory survey. This involves assaying by multiple laboratories from around the world. Results are compiled into a comprehensive report detailing statistics for each standard. Assay distributions are checked and processed statistically, producing monitoring statistics for these standards. Materials are tested regularly to ensure stability and homogeneity.

Stability

This product remains stable in its original packaging, away from direct sunlight.

Material Safety

This product is not hazardous and non-toxic.

Neutron Activation Analysis Results (ppm, unless otherwise noted)

Antimony	69.8
Arsenic	404.5
Barium	1850
Bromine	<1.2
Cadmium	337
Caesium	1.3
Calcium (%)	nr
Cerium	164
Chromium	56.5
Cobalt	96.5
Europium	1.75
Gold (ppb)	5510
Hafnium	7
Iridium (ppb)	<50
Iron (%)	4.35
Lanthanum	91
Lutetium	0.55
Mercury	nr
Molybdenum	53.5
Neodymium	nr
Nickel	60
Potassium (%)	nr
Rubidium	106.5
Samarium	10.95
Scandium	5.85
Selenium	<5
Silver	15.5
Sodium (%)	1.71
Strontium	nr
Tantalum	1.1
Tellurium	<10
Terbium	1.15
Thorium	29.3
Tin	<100
Tungsten	8
Uranium	3.95
Ytterbium	2.95
Zinc	66000
Zirconium	<200

Major Elements by Fusion / XRF (%)

Fe	4.62
SiO ₂	53.35
Al ₂ O ₃	11.67
TiO ₂	0.47
MnO	0.05
CaO	2.08
P	0.092
S	5.78
MgO	1.14
K ₂ O	3.62
Na ₂ O	2.76
LOI1000	7.35

Neutron Activation Analyses and Fusion / XRF Analyses are single results and are indicative only. These are provided for matrix identification purposes.

'nr': Not Reported

20 Hines Road, O'Connor, Western Australia 6163
Phone: +61 8 9314 2566 | Email: info@geostats.com.au
Website: www.geostats.com.au

GBM919-13

Geostats Pty Ltd, Certified Ore Grade Base Metal Reference Material, Product Code: