

GEOSTATS PTY LTD

Mining Industry Consultants
Reference Material Manufacture and Sales

Certified Geochem Base Metal Reference Material Product Code

GBM921-3

Certified Control Values

Total Digest

Element	Grade	Standard Deviation	Num of Analyses	Confidence Interval
Nickel (ppm)	45	2	62	+/- 0.6
Copper (ppm)	38	2	56	+/- 0.7
Zinc (ppm)	476	26	66	+/- 6.5
Lead (ppm)	63	5	58	+/- 1.2
Arsenic (ppm)	100	6	58	+/- 1.5
Cobalt (ppm)	19	1	61	+/- 0.3
Silver (ppm)	1.6	0.2	49	+/- 0.05

Partial Digest

Element	Grade	Standard Deviation	Num of Analyses	Confidence Interval
Nickel (ppm)	44	3	58	+/- 0.7
Copper (ppm)	36	2	73	+/- 0.5
Zinc (ppm)	471	25	71	+/- 6.1
Lead (ppm)	62	5	65	+/- 1.2
Arsenic (ppm)	87	18	68	+/- 4.4
Cobalt (ppm)	18	1	61	+/- 0.4
Silver (ppm)	1.6	0.3	69	+/- 0.07

CRM Details

<u>Control Statistic Details</u>		Neutron Activation Analysis Results (ppm, unless otherwise noted)		Major Elements by Fusion / XRF (%)	
Control statistics were produced from results accumulated in the October-2021 round robin. The number of results used to certify each analyte is shown in the table above.		Antimony	8.5	Fe	3.9
		Arsenic	103	SiO ₂	59.29
		Barium	298	Al ₂ O ₃	14.14
		Bromine	<2	TiO ₂	0.62
		Cadmium	<10	MnO	0.59
		Caesium	8	CaO	4.02
		Calcium (%)	nr	P	0.054
		Cerium	34	S	1.59
		Chromium	79	MgO	2.02
		Cobalt	18.3	K ₂ O	3.2
		Europium	0.7	Na ₂ O	0.39
		Gold (ppb)	<5	LOI1000	7.85
		Hafnium	<5	Neutron Activation Analyses and Fusion / XRF Analyses are single results and are indicative only. These are provided for matrix identification purposes. 'nr': Not Reported	
		Iridium (ppb)	<50		
		Iron (%)	3.8		
		Lanthanum	18		
		Lutetium	0.2		
		Mercury	nr		
		Molybdenum	<10		
		Neodymium	nr		
		Nickel	47		
		Potassium (%)	nr		
		Rubidium	100		
		Samarium	3.1		
		Scandium	11		
		Selenium	<10		
		Silver	<5		
		Sodium (%)	0.282		
		Strontium	nr		
		Tantalum	<2		
		Tellurium	<20		
		Terbium	<1		
		Thorium	4.9		
		Tin	<200		
		Tungsten	2		
		Uranium	1		
		Ytterbium	1.5		
		Zinc	490		
		Zirconium	<500		
<u>Material Description</u>					
This material is described as a Fresh rhyolite, Pilbara, WA.					
<u>Colour Designation (ISCC-NBS, SP440)</u>					
This material is very light gray in colour.					
<u>Usage</u>					
This product is for use in the mining industry as a reference material for monitoring and testing the accuracy of laboratory assaying.					
<u>Preparation and Packaging</u>					
All CRMs are dried in an oven for a minimum of 12 hours at 110°C. The dry material is then pulverised to better than 75 micron (nominal mean of 45 micron) using an air classifier. The material is then homogenised and stored in a sealed, stable container ready for final packaging.					
Materials are statistically sampled from stores, then packaged into either heat sealed, air tight, plastic pulp packets or screw top sealed plastic containers ready for distribution. All packaging has been chosen to ensure minimal contamination from outside sources during shipment, use and storage.					
<u>Assay Testwork</u>					
All standards are tested thoroughly in the Geostats bi-annual laboratory survey. This involves assaying by multiple laboratories from around the world. Results are compiled into a comprehensive report detailing statistics for each standard. Assay distributions are checked and processed statistically, producing monitoring statistics for these standards. Materials are tested regularly to ensure stability and homogeneity.					
<u>Stability</u>					
This product remains stable in its original packaging, away from direct sunlight.					
<u>Material Safety</u>					
This product is not hazardous and non-toxic.					

20 Hines Road, O'Connor, Western Australia 6163
Phone: +61 8 9314 2566 | Email: info@geostats.com.au
Website: www.geostats.com.au

GBM921-3

Geostats Pty Ltd, Certified Geochem Base Metal Reference Material, Product Code: