

GEOSTATS PTY LTD

Mining Industry Consultants
Reference Material Manufacture and Sales

Certified Geochem Base Metal Reference Material Product Code

GBM921-7



Certified Control Values

Total Digest

Element	Grade	Standard Deviation	Num of Analyses	Confidence Interval
Nickel (ppm)	42	4	62	+/- 1
Copper (ppm)	5834	222	69	+/- 53.8
Zinc (ppm)	9688	328	63	+/- 83.3
Lead (ppm)	3048	293	67	+/- 71.9
Arsenic (ppm)	346	29	59	+/- 7.6
Cobalt (ppm)	42	2	58	+/- 0.5
Silver (ppm)	19.2	1.0	60	+/- 0.25

Partial Digest

Element	Grade	Standard Deviation	Num of Analyses	Confidence Interval
Nickel (ppm)	27	3	54	+/- 0.9
Copper (ppm)	5878	197	86	+/- 42.5
Zinc (ppm)	9890	460	64	+/- 115.8
Lead (ppm)	3158	226	72	+/- 53.6
Arsenic (ppm)	351	33	65	+/- 8.4
Cobalt (ppm)	29	3	63	+/- 0.8
Silver (ppm)	19.2	1.0	78	+/- 0.23

CRM Details

Control Statistic Details		Neutron Activation Analysis Results (ppm, unless otherwise noted)		Major Elements by Fusion / XRF (%)	
Control statistics were produced from results accumulated in the October-2021 round robin. The number of results used to certify each analyte is shown in the table above.		Antimony	116	Fe	6.3
		Arsenic	360	SiO ₂	57.13
		Barium	325	Al ₂ O ₃	13.84
		Bromine	<2	TiO ₂	1.173
		Cadmium	21.9	MnO	0.13
		Caesium	2	CaO	6.01
		Calcium (%)	nr	P	0.06
		Cerium	37	S	1.13
		Chromium	110	MgO	3.55
		Cobalt	44.5	K ₂ O	1.89
		Europium	1.1	Na ₂ O	3.181
		Gold (ppb)	481	LOH1000	1.17
		Hafnium	<5	Neutron Activation Analyses and Fusion / XRF Analyses are single results and are indicative only. These are provided for matrix identification purposes. 'nr': Not Reported	
		Iridium (ppb)	<50		
		Iron (%)	6.6		
		Lanthanum	19		
		Lutetium	0.4		
		Mercury	nr		
		Molybdenum	53		
		Neodymium	nr		
		Nickel	57		
		Potassium (%)	nr		
		Rubidium	80		
		Samarium	4.5		
		Scandium	20.9		
		Selenium	<10		
		Silver	20		
		Sodium (%)	2.35		
		Strontium	nr		
		Tantalum	<2		
		Tellurium	<20		
		Terbium	1		
		Thorium	11.1		
		Tin	<200		
		Tungsten	<2		
		Uranium	6		
		Ytterbium	2.7		
		Zinc	10200		
		Zirconium	<500		

Material Description	
This material is described as a Low Cu Pb Zn .	

Colour Designation (ISCC-NBS, SP440)	
This material is med. light gray in colour.	

Usage	
This product is for use in the mining industry as a reference material for monitoring and testing the accuracy of laboratory assaying.	

Preparation and Packaging	
All CRMs are dried in an oven for a minimum of 12 hours at 110°C. The dry material is then pulverised to better than 75 micron (nominal mean of 45 micron) using an air classifier. The material is then homogenised and stored in a sealed, stable container ready for final packaging.	
Materials are statistically sampled from stores, then packaged into either heat sealed, air tight, plastic pulp packets or screw top sealed plastic containers ready for distribution. All packaging has been chosen to ensure minimal contamination from outside sources during shipment, use and storage.	

Assay Testwork	
All standards are tested thoroughly in the Geostats bi-annual laboratory survey. This involves assaying by multiple laboratories from around the world. Results are compiled into a comprehensive report detailing statistics for each standard. Assay distributions are checked and processed statistically, producing monitoring statistics for these standards. Materials are tested regularly to ensure stability and homogeneity.	

Stability	
This product remains stable in its original packaging, away from direct sunlight.	

Material Safety	
This product is not hazardous and non-toxic.	

20 Hines Road, O'Connor, Western Australia 6163
Phone: +61 8 9314 2566 | Email: info@geostats.com.au
Website: www.geostats.com.au

GBM921-7

Geostats Pty Ltd, Certified Geochem Base Metal Reference Material, Product Code: