Major Elements by

GEOSTATS PTY LTD

Mining Industry Consultants
Reference Material Manufacture and Sales

Certified Low Level Gold Reference Material Product Code

GLG320-1

Certified Control Values

Low Level Gold

Gold Grade 322.15 ppb

Standard Deviation 17.56 ppb

Confidence Interval +/- 3.81 ppb



Neutron Activation

CRM Details

	Analysis Results (ppm, unless otherwise noted)		Fusion / XRF (%)	
Control Statistic Details				
Control statistics were produced from results accumulated in the April-2020				
round robin. A total of 85 gold assays were used to certify this material.	Antimony	<0.1	Fe	5.14
	Arsenic	<0.5	SiO ₂	62.36
	Barium	431	Al ₂ O ₃	14.17
Material Description	Bromine	<2	TiO ₂	1.06
This material is described as a Milled low grade halo.	Cadmium	<10	MnO	0.1
	Caesium	<2	CaO	5.63
	Calcium (%)	nr	Р	0.052
Colour Designation (ISCC-NBS, SP440)	Cerium	38	S	0.08
This material is light gray in colour.	Chromium	108	MgO	3.26
	Cobalt	23	K ₂ O	2.15
<u>Usage</u>	Europium	1.1	Na ₂ O	3.3
This product is for use in the mining industry as a reference material for	Gold (ppb)	353	LOI1000	0.4
monitoring and testing the accuracy of laboratory assaying.	Hafnium	<5		
	Iridium (ppb)	<50	Neutron Activation	
Preparation and Packaging	Iron (%)	5.4	Analyses and Fusion /	
All CRMs are dried in an oven for a minimum of 12 hours at 110°C. The dry	Lanthanum	18	XRF Analyses are	
material is then pulverised to better than 75 micron (nominal mean of 45 micron)	Lutetium	0.4	single results and are	
using an air classifier. The material is then homogenised and stored in a sealed,	Mercury	nr	J G	
stable container ready for final packaging.	Molybdenum	<10	indicative only. These	
	Neodymium	nr	are provided for matrix	
Materials are statistically sampled from stores, then packaged into either heat	Nickel	25	identification purposes.	
sealed, air tight, plastic pulp packets or screw top sealed plastic containers ready	Potassium (%)	nr		
for distribution. All packaging has been chosen to ensure minimal contamination	Rubidium	· · · · · · · · · · · · · · · · · · ·		orted
from outside sources during shipment, use and storage.	Samarium	4.6		
	Scandium	18.8		
Assay Testwork	Selenium	<10		
All standards are tested thoroughly in the Geostats bi-annual laboratory survey.	Silver	<5		
This involves assaying by multiple laboratories from around the world. Results	Sodium (%)	2.43		
are compiled into a comprehensive report detailing statistics for each standard.	Strontium	nr		
Assay distributions are checked and processed statistically, producing	Tantalum	2		
monitoring statistics for these standards. Materials are tested regularly to ensure	Tellurium	<20		
stability and homogeneity.	Terbium	<1		
	Thorium	12		
Stability	Tin	<200		
This product remains stable in its original packaging, away from direct sunlight.	Tungsten	<5		
	Uranium	7		
Material Safety	Ytterbium	2.7		

20 Hines Road, O'Connor, Western Australia 6163
Phone: +61 8 9314 2566 | Email: info@geostats.com.au
Website: www.geostats.com.au

Zinc

Zirconium

<200

<500

This product is not hazardous and non-toxic.