


GEOSTATS PTY LTD

Mining Industry Consultants
Reference Material Manufacture and Sales

Certified Ore Grade Base Metal Reference Material Product Code

GBM923-15

Certified Control Values



Element	Grade	Standard Deviation	Num of Analyses	Confidence Interval
Nickel (ppm)	74	12	104	+/- 2
Copper (ppm)	14439	482	303	+/- 55
Zinc (ppm)	31010	1377	264	+/- 167
Lead (ppm)	10694	603	262	+/- 73
Cobalt (ppm)	nr	nr	nr	nr
Silver (ppm)	19.4	1.5	264	+/- 0.18
Sulphur (%)	3.27	0.12	217	+/- 0.02

CRM Details

Control Statistic Details

Control statistics were produced from results accumulated in the April-2011, April-2012, October-2023 round robins. The number of results used to certify each analyte is shown in the table above.

Material Description

This material is described as a Low copper zinc cap material.

Colour Designation (ISCC-NBS, SP440)

This material is light gray in colour.

Usage

This product is for use in the mining industry as a reference material for monitoring and testing the accuracy of laboratory assaying.

Preparation and Packaging

All CRMs are dried in an oven for a minimum of 12 hours at 110°C. The dry material is then pulverised to better than 75 micron (nominal mean of 45 micron) using an air classifier. The material is then homogenised and stored in a sealed, stable container ready for final packaging.

Materials are statistically sampled from stores, then packaged into either heat sealed, air tight, plastic pulp packets or screw top sealed plastic containers ready for distribution. All packaging has been chosen to ensure minimal contamination from outside sources during shipment, use and storage.

Assay Testwork

All standards are tested thoroughly in the Geostats bi-annual laboratory survey. This involves assaying by multiple laboratories from around the world. Results are compiled into a comprehensive report detailing statistics for each standard. Assay distributions are checked and processed statistically, producing monitoring statistics for these standards. Materials are tested regularly to ensure stability and homogeneity.

Stability

This product remains stable in its original packaging, away from direct sunlight.

Material Safety

This product is not hazardous and non-toxic.

Neutron Activation

Analysis Results (ppm, unless otherwise noted)

Antimony	431
Arsenic	1320
Barium	415
Bromine	<2
Cadmium	54
Caesium	<2
Calcium (%)	nr
Cerium	30
Chromium	102
Cobalt	73
Europium	1.2
Gold (ppb)	1090
Hafnium	<5
Iridium (ppb)	<50
Iron (%)	7.4
Lanthanum	18
Lutetium	0.4
Mercury	nr
Molybdenum	<10
Neodymium	nr
Nickel	<100
Potassium (%)	nr
Rubidium	76
Samarium	4.1
Scandium	20
Selenium	21
Silver	21
Sodium (%)	2.14
Strontium	nr
Tantalum	<2
Tellurium	<20
Terbium	<1
Thorium	9.9
Tin	<200
Tungsten	3
Uranium	5
Ytterbium	2.4
Zinc	33000
Zirconium	<500

Major Elements by Fusion / XRF (%)

Fe	6.38
SiO ₂	52.3
Al ₂ O ₃	12.68
TiO ₂	1.102
MnO	0.14
CaO	5.44
P	0.059
S	3.37
MgO	3.22
K ₂ O	1.72
Na ₂ O	3.044
LOI1000	2.02

Neutron Activation Analyses and Fusion / XRF Analyses are single results and are indicative only. These are provided for matrix identification purposes.

'nr': Not Reported

20 Hines Road, O'Connor, Western Australia 6163
Phone: +61 8 9314 2566 | Email: info@geostats.com.au
Website: www.geostats.com.au

GBM923-15

Geostats Pty Ltd, Certified Ore Grade Base Metal Reference Material, Product Code: